DECLARATION OF PERFORMANCE (DOP)

| | NO. 99211601 CPR-20200110 | |
|----|---|---|
| 1. | Product Type: | Freestanding stove ILD |
| 2. | Type, batch or serial number: | ILD 11 ECO-HE |
| 3. | Intended use of the product: | Heat distribution/room heating Without hot water supply Fuel type: Wood |
| 4. | Name and Address of the manufacturer: | For: Scan A/S · Damsbovej 1 · DK-5492 Vissenbjerg |
| | | By: COLOR EMAJL · D.O.O. · Alaginci 87/a · Pozega · Croatia |
| 5. | Contact address: | No relevance |
| 6. | AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V | System 3 |
| 7. | Notified body: Test report no: | DTI NB-No 1235 300-ELAB-2489-EN nom |
| 8. | Declared performance | 300 EE/IS E IOS EIVIIOIII |
| 0. | Harmonized technical specification | EN 13240:2001/A2:2004/AC:2007 |
| | Essential characteristics | Performance |
| | Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out | A1 Minimum distances in mm: Rear: 225 Sides: 400 Front: 1050 NPD |
| | Emission of combustion products | CO [880 mg/Nm³] NOx [89 mg/Nm³] OGC [58 mg/Nm³] Dust [24 mg/Nm³] |
| | Surface temperature | Pass |
| | Electrical safety | - |
| | Cleanability | Pass |
| | Maximum water operating pressure | - |
| | Flue gas temperature at nominal heat output [EN] | T[132°C] |
| | Mechanical resistance (to carry a chimney/flue) | NPD |
| | Thermal output Room heating output Water heating output | 8 kW - - |
| | Energy efficiency | ŋ [90 %] |

DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Brian Steen Ørum, Senior Project Manager)

Vissenbjerg, 10.01.2020



